Flood Impact Assessment

Proposed Aged Care Facility at Bulli

8201813802

Prepared for Anglicare

17 August 2018







Contact Information

Cardno (NSW/ACT) Pty Ltd Prepared for Anglicare

ABN 95 001 145 035

Project Name Proposed Aged Care Facility

Document Information

16 Burelli Street at Bulli

Wollongong 2500 File Reference Document1

Australia

Job Reference 8201813802

Phone +612 4228 4133 Date 17 August 2018

Fax +612 4228 6811 Version Number 1

Author(s):

Ali Djozan Effective Date 17/08/2018

Senior Water Engineer

Approved By:

Rory Hentschel Date Approved 17/08/2018

Manager Water

Document History

Version	Effective Date	Description of Revision	Prepared by	Reviewed by
1	08 August 2018	Issued for S75W	Ali Djozan	Rory Hentschel
2	17 August 2018	Issued for S75W	Ali Djozan	Rory Hentschel

[©] Cardno. Copyright in the whole and every part of this document belongs to Cardno and may not be used, sold, transferred, copied or reproduced in whole or in part in any manner or form or in or on any media to any person other than by agreement with Cardno.

This document is produced by Cardno solely for the benefit and use by the client in accordance with the terms of the engagement. Cardno does not and shall not assume any responsibility or liability whatsoever to any third party arising out of any use or reliance by any third party on the content of this document.



Table of Contents

1	Introduc	tion	1
	1.1	Background	1
	1.2	Study Area	1
	1.3	Purpose of this Report	1
2	Available	e Data	3
	2.1	Topographic data	3
	2.2	Previous Studies	3
3	Hydrolog	ЗУ	4
	3.1	Catchment Description	4
	3.2	Hydrological Model Selection	6
	3.3	Model Input	6
	3.4	Design Storm Results	7
4	Hydrauli	cs	8
	4.1	Selection of Hydraulic Model	8
	4.2	Model Geometry, Boundary Conditions and Roughness	8
	4.3	Existing Hydraulic Structures Modelled	9
	4.4	Culverts Blockage	9
	4.5	Pre-Development Scenario	12
	4.6	Post-Development Scenario	12
5	Stormwa	ater Drainage Concept	13
6	Conclusi	on	15

Appendices

Appendix A WBNM Input parameters

Appendix B WBNM results

Appendix C Flood Result Maps

Appendix D Site Survey

Tables

Table 3-1	Rainfall data	6
Table 3-2	WBNM Parameters	6
Table 4-1	Manning's n Values	8
Table 4-2	Existing Culverts Configurations	9



Figures

Figure 1-1	Proposed Development Plan	2
Figure 3-1	Catchment Plan	5
Figure 4-1	Hydraulic Model Schematization	10
Figure 4-2	Spatial Distribution of manning's n	11
Figure 5-1	Drainage Concept Plan	14



1 Introduction

1.1 Background

Anglicare are proposing to develop an aged care facility at lot 2 & 3 DP 1176767 at Bulli, NSW. Cardno has been commissioned to carry out a flood impacts assessment to support the concept plan modification application for the subject development.

1.2 Study Area

The site proposed for the development is located in Geragthy Street in Bulli. The subject site is bounded with Geragthy Street and railway line to the west (railway line runs immediately upstream and parallel to Geragthy Street), Wilkies Street to the north and Sandon Drive to the south. Refer to **Figure 1-1** for locality of the subject site.

Tramway Creek runs along the southern side of the subject site and joins Woodland Creek further downstream before discharging into the ocean. Cookson Creek (a tributary of Tramway Creek) runs through the middle of the site.

The subject site generally falls in an easterly direction (towards the ocean). However, the northern part of the site is located on a hill side and has a steep southerly fall towards Cookson Creek running through the middle of the site. The site levels vary between RL26.8m AHD in north-western corner of the site and RL5.2m AHD in the eastern side of the site and within the Cookson Creek.

Based on the topography, Cookson Creek collects a local catchment mostly comprising the subject site with some area to the western side of the railway line.

1.3 Purpose of this Report

The main objective for this report is to undertake a flood study for Tramway Creek and an impacts assessment for the proposed aged care facility development. Specifically, this flood study aims to:

- > Determine the flood behaviour on the development site (flood extent, flood levels, flood depth and flood velocities) for a range of design events up to and including 100 year ARI design event and PMF.
- > Ensure that the majority of land within the development site will be located on land above the PMF and as such is not subject to flood related planning controls or located on flood prone land.
- > Ensure that no detrimental offsite impacts are created in the 1% AEP and PMF events as a result of the proposed development.
- Review the previous drainage concept from the concept approval and update it to reflect the currently proposed layout.



Figure 1-1 Proposed Development Plan



2 Available Data

2.1 Topographic data

2.1.1 Aerial Laser Scanning (ALS) Survey

ALS (taken in 2013) data was sourced from Land and Property Information (LPI) and used for undertaking the catchment delineation, hydrology modelling and hydraulic modelling for this study.

2.1.2 Ground Survey

Detailed survey data within the site was captured by Dennis Smith Surveyors on the 19th January 2006 and has been incorporated into the hydraulic model to better represent the topography of the study area. A pdf copy of the survey is included in **Appendix D**.

2.2 Previous Studies

2.2.1 Review of Hewitt Creek Flood Study (WBNM, August 2015)

Review of Hewitt Creek Flood Study (RHCFS) was prepared for Wollongong City Council (WCC) to determine the flood behaviour in the Hewitt Creek study area and consider influence of potential climate change on future flood behaviour.

The RHCFS developed a WBNM model for hydrological assessment of the study catchment. The WBNM model was calibrated and validated to April 1988, August 1998 and February 2013 events. A TUFLOW two-dimensional hydraulic model was developed as part of this study. The TUFLOW model was also calibrated and validated similarly.

RHCFS is relevant to this current study as it covers the site, the Tramway Creek catchment and Slacky Creek catchment which are relevant to this current study.

The catchment plan provided in RHCFS have been used as a basis in undertaking the catchment delineation for this current study. The hydrological parameters (such as rainfall loss values and routing lagging factors) have been adopted consistent with RHCFS for this current study.

This report has been also used a basis for comparison of our modelling results in terms of general parity in the flooding extent.

2.2.2 Addendum to Flood Study Report for Anglican Retirement Village (GHD, May 2006)

This report was also reviewed as one of the earliest hydraulic studies prepared for the proposed development.

This study adopted the boundary conditions from the Hewitt Creek Flood Study (an earlier version) and then developed a HEC-RAS model for Tramway Creek reach extending up to just downstream of the railway and the culvert underneath of it.

This study was not identified suitable for comparison of our model results because of the followings:

- > The GHD report does not cover the Cookson's Creek
- > It does not account for the hydraulic constraints imposed by the railway culvert on Tramway Creek



3 Hydrology

3.1 Catchment Description

The proposed development site is located within the downstream reaches of Tramway Creek. Tramway Creek runs parallel to the southern boundary of the site. Cookson Creek, a tributary of Tramway Creek, runs through the site and joins the Tramway Creek just downstream of the site. Tramway Creek then joins the Woodland Creeks Creek just before discharging to the ocean.

Cookson Creek mostly drains the site with some external catchment to the west of Geragthy Street and the Illawarra Railway totalling a catchment area of approximately 12ha. Levels in Cookson Creek catchment varies between approximately RL 4m AHD in the confluence point with Tramway Creek to RL 35m AHD to adjacent to the Illawarra Railway.

Tramway Creek drains a larger catchment extending from Tramway Creek and Woodlands Creek confluence just east of the site to areas to the west of the Princes Highway, north of Bulli Showground and Racing Complex and north of Hobart Street. Tramway Creek totals a catchment area of approximately 30ha. The elevations in Tramway Creek catchment variy between RL4 m AHD at the confluence with Cookson Creek to RL42 m AHD at the north-western end of the catchment.


Slacky Creek covers an area of approximately 248ha. There are a number of drainage structures along Slacky Creek including the Hobart Street culverts crossing, old coal haulage railway culverts crossing, Princes Highway Culverts Crossing and Illawarra Railway Culvert crossing. The Hobart Street Culverts crossing and old coal haulage railway culverts crossing provide significant obstruction against Slacky Creek conveyance and divert significant flows into the Tramway Creek catchment. Further break outs from Slacky Creek are predicted to occur just to the north east of the Bulli Showground and Racing Complex.

The Slacky Creek catchment has been included in this study to allow quantification of this cross catchment from between Slacky Creek and the Tramway Creek catchment. Slacky Creek catchment has been modelled down to the Illawarra Railway crossing.

Figure 3-1 shows the catchment delineation for the study area including Cookson Creek, Tramway Creek and Slacky Creek.



Figure 3-1 Catchment Plan





3.2 Hydrological Model Selection

The computer model 'Watershed Bounded Network Model' WBNM2007 v104 (Boyd et al, 2007) was used for hydrological modelling of the study area. WBNM is an advanced storage-routing model that allows simulation of complex catchment behaviour. This particular model was considered most appropriate to the task of modelling the study area, given its ability to model a wide range of catchment characteristics and its local development, the model allowed peak flows to be established at various locations throughout the subject site.

3.3 Model Input

3.3.1 Sub-Catchment Topology

Sub-catchment topology for the constructed model reflected input from:

- > ALS data purchased from LPI to represent the existing surface.
- > Aerial photography from NearMap for the establishment of impervious/pervious areas across the floodplain

Sub-catchments were delineated from the total catchment (290 ha) in order to accurately model the peak flows and flood extents over the site.

The sub-catchment delineation developed and used in the hydrologic model is presented in **Figure 3-1**. There is a generally parity between the catchment delineation undertaken by Cardno and the catchment delineation presented in WBNM report.

3.3.2 Impervious Fraction

The impervious area for each sub-catchment was estimated using the most recently available aerial photography from nearmap. The surface area of impervious features was determined as a percentage of the individual sub-catchment areas and an impervious factor was assigned to each, which represented the type and density of impervious features present. It was assumed that the impervious fraction of residential areas was approximately 70%.

The WBNM data presented in **Appendix A** shows the final estimated impervious fractions for each sub-catchment (Pre-Development Scenario).

3.3.3 Rainfall data

Rainfall data for the site was sourced from the Bureau of Meteorology (BOM). The data used to generate the design storm bursts in the WBNM model is presented in **Table 3-1**.

Table 3-1 Rainfall data

Parameter	Value
2 Year 1 Hour Intensity	46 mm/hr
2 Year 12 Hour Intensity	11.1 mm/hr
2 Year 72 Hour Intensity	4.15 mm/hr
50 Year 1 Hour Intensity	102 mm/hr
50 Year 12 Hour Intensity	26.3 mm/hr
50 Year 72 Hour Intensity	9 mm/hr
F2 Geographic Factor	4.28
F50 Geographic Factor	15.8
Location Skew Coefficient	0.0

3.3.4 Hydrological parameters

The hydrological parameters used for input to the WBNM model are listed in **Table 3-2**.

Table 3-2 WBNM Parameters

|--|



Initial loss (pervious surface)	0 mm	Conservatively taken as zero.
Initial loss (impervious surface)	0 mm	Conservatively taken as zero.
Continuing loss (pervious surface)	2.5 mm/hr	AR&R recommends 2.5 mm/hr for ungauged NSW catchments
C (Catchment Lag parameter)	1.29	Regional calibration value
Impervious Lag	0.1	WBNM default <u>value</u>
Stream Lag	1.0	Model default

3.4 Design Storm Results

The WBNM hydrological model was simulated against a range of design storm events to determine the critical design storm duration. The ARI storm events analysed in this study included the 100 year ARI design events and the probable maximum flood (PMF). The identified critical durations to assess the proposed development were 2 hours for 100 year ARI storm events and 60 minutes for the PMF.

Results from the WBNM model is provided in **Appendix B**.



4 Hydraulics

4.1 Selection of Hydraulic Model

The TUFLOW 2D model was used in the hydraulic assessment of the study area. A 2D model was selected to model the floodplain in order to better represent the complex hydraulics associated with floodplain areas. The model extent was determined based on review of the topography of the study area and review of the previous flood studies to ensure that significant hydraulic controls and flow break out points are incorporated. The downstream boundary was set up at a location downstream of the site to ensure that an accurate tailwater condition is established.

4.2 Model Geometry, Boundary Conditions and Roughness

The TUFLOW model was established over a 2.5 meter grid, with elevations extracted from the topographic data discussed in **Section 2.1**.

The flood behaviour on the proposed development site is generally controlled by Tramway Creek running parallel to the southern boundary of the site and Cookson Creek (a tributary of Tramway Creek) running through the site. The Tramway Creek system is expected to be of higher importance as it conveys a significantly greater catchment compared to Cookson Creek.

The Slacky creek system was also incorporated to the TUFLOW model to an extent downstream enough (just downstream of Princes Highway) to ensure that any diversion and break out from Slacky Creek to Tramway Creek is simulated.

The outflow boundary condition has been set up at the location of the confluence of Cookson Creek and Tramway Creek which is upstream from the ocean discharge. A H_Q outflow boundary condition has been defined in TUFLOW model for this boundary. The outflow boundary was set at a location far enough downstream of the site to ensure that the model establishes an accurate tailwater condition. A number of sensitivity scenarios were set up and run to investigate the potential impacts tidal changes on the flood behaviour around the study area. The results of the sensitivity scenarios show that the flood levels at the proposed development site are not anticipated to be impacted by the tide significantly. Therefore, no tidal downstream boundary condition was set for this model.

Inflow hydrographs from the WBNM model were applied to the upstream catchments, ensuring enough routing time/distance, to allow the model to stabilise and accurately predict flooding behaviour at the site. The hydraulic model schematisation for the TUFLOW model is shown in **Figure 4-1**.

Roughness areas across the TUFLOW modelling domain were digitised based on aerial imagery and site inspection. The Manning's roughness values adopted in the hydraulic model are presented in **Table 4-1**. The spatial distribution of Manning's n adopted in the TUFLOW model are shown in **Figure 4-2**.

Table 4-1 Manning's n Values

Land Use Type	Manning's n Value
Forests/Dense vegetation	0.09
Open Space/Parkland	0.04
Lumped Urban Residential	1.0
Creek-Lightly Vegetated	0.05
Creek-Heavily Vegetated	0.09
Rail Corridor	0.08
Roads/Pavement	0.02
Buildings	1.0



4.3 Existing Hydraulic Structures Modelled

The major existing hydraulic structures within the study areas were identified and incorporated to the predevelopment scenario. The location and description of the structures is shown on **Figure 4-1**. The configuration of the proposed culvert structures is provided in **Table 4-2**. The information regarding the hydraulic structures was sourced from RHCFS and was verified by a site visit undertaken to observe all of these structures.

Table 4-2 Existing Culverts Configurations

Structure ID	Watercourse	Street or Landmark	Structure Type	Culvert Configurations
1	Cookson Creek	Geragthy Street	Culvert	(1x) 675 RCP
2	Cookson Creek	Illawarra Railway	Culvert	(1×) 600 RCP
3	Tramway Creek	Illawarra Railway	Culvert	(1x) 2100 RCP
4	Slacky Creek	Illawarra Railway Underpass	Culvert	(1x) 4800x4050 RCBC
5	Slacky Creek	Illawarra Railway	Culvert	(1x) 4800x5900 RCBC
6	Slacky Creek	Footbridge	Culvert	(2x) 2850x3000 RCBC
7	Slacky Creek	Princes Highway	Culvert	(4×) 2440×1680 RCBC
8	Slacky Creek	Old Coal Haulage Railway	Culvert	(3×) 2750×1700 RCBC
9	Slacky Creek	Hobart Street	Culvert	(3x) 1200 RCP

4.4 Culverts Blockage


The hydraulic assessment in our study included a blockage scenario applied to the culverts for both predevelopment and post development scenarios.

The blockage factors applied to the culverts are in accordance with Wollongong City Council's Review of Conduits Blockage Policy Summary Report-Final dated June 2016.

Two scenarios of blocked and un-blocked were run for the pre-development and post-development scenarios with the worst case scenario extracted and presented in the results and maps.



Figure 4-1 Hydraulic Model Schematization






Hydraulic Model Schematization

PROPOSED AGED CARE FACILITY AT BULLI, NSW


Legend





Site Boundary



Watercourse (LPI)








Hydraulic Model Extent

FIGURE 4-1 1:6,000 Scale at A3








Map Produced by Cardno NSW/ACT Pty Ltd (WOL) Date: 2018-08-14 | Project: 82018138_02 Coordinate System: GDA 1994 MGA Zone 56 Map: 82018138-02-GS-003_HydraulicModel.mxd 03 Aerial imagery supplied by nearmap (May, 2018)



Figure 4-2 Spatial Distribution of manning's n





4.5 Pre-Development Scenario

The model set up for the pre-development scenario was run for the 100 year ARI design event and the PMF. The pre-development simulation results are presented in **Appendix C**.

The existing culverts under the Illawarra Railway and Geraghty Street do not have sufficient capacity to convey the 100 year ARI design event. Therefore, it is predicted that the Illawarra Railway and Geragthy Street will be overtopped by the 100 year ARI design event from Cookson's Creek catchment. The flow conveyed by the culverts is predicted to discharge into Cookson's Creek. The flows overtopping the railway embankment are predicted to flow south along Geragthy Street and then flood the site in a 100 year ARI design event. A more severe flooding of the site from Cookson's creek catchment is anticipated in PMF.

The flood behaviour in Tramway Creek represents a more complex situation. Significant flows from Slacky Creek are predicted to be diverted into the Tramway catchment in a 100 year ARI design event and greater events up to and including PMF. This is a result of the controls imposed by the culverts under Hobart Street and the disused Bulli Colliery railway. The flows diverted from Slacky Creek and the flows from the Tramway Creek are directed into a single 2.1m RCP pipe culvert under the Illawarra Railway just upstream of the proposed development site. Significant headwater is predicted upstream of this culvert in a 100 year ARI design event. However, no overtopping of the rail at the location of this culvert is predicted in the flows up to and including 100 year ARI design event. Significant overtopping of the Illawarra Railway is expected at this location in PMF. Tramway Creek is predicted to overtop the rail embankment in PMF and then flood the proposed development site.

4.6 Post-Development Scenario

A post-development scenario was set up based on the pre-development scenario and incorporating the following updates:

- > The design surface levels for the proposed development. The residential development level was determined based on the PMF flood level.
- > Incorporate the sound barrier wall to the western boundary of the site. A sound barrier wall was required to be installed between the proposed development site and the railway corridor. However, this wall will be designed to act as flood barrier as well.
- Make the existing pipe under the Geragthy Street redundant (due to conflict with the proposed layout) and incorporate a new culvert to discharge into the Cookson's Creek within the site in a location to the south of the existing discharge point. Refer to Figure 1-1 (proposed development plan) for more details on the culverts modifications arrangement).

The post-development scenario was run for the 100 year ARI design event and the PMF. The flood result maps for the post development scenario as well as the impact maps are in Appendix C.

The proposed sound barrier is predicted to provide significant flood mitigation benefits for the proposed development in 100 year ARI design event and PMF. Flows overtopping the railway from the Tramway Creek will be diverted from the proposed site by the wall from the site into the railway drain and ultimately into the Tramway Creek. The flows overtopping the rail from Cookson's creek catchment will be collected by a proposed culvert system behind the wall and will convey the flows into the Cookson's Creek within the site.

4.6.1 Impacts

An impacts assessment was undertaken by comparing the post-development results to the pre-development results for 100 year ARI design event and PMF.

The proposed development is expected to result in increases in Maximum Water Surface Elevation of generally less than 100mm and up to 250mm is limited spots along the Cookson Creek (within the site) in a 100 year ARI design events. No impacts is predicted within the rail corridor as a result of the proposed development in a 100 year ARI design event.

Increases in Maximum Water Surface Elevation of up to 100mm are predicted within Cookson's Creek within the site as a result of the proposed development in PMF. Increase in Maximum Water Surface Elevation of generally less than 100mm (and up to 350mm in localised areas) is anticipated within Tramway Creek as a result of the proposed development (to the south of the proposed site) in PMF. Increases in Maximum Water Surface Elevation of up to 1000mm are expected against the proposed sound barrier wall within the rail corridor. However, these impacts are limited to the drains within the rail corridor with no impacts on the rail formation level in PMF.



5 Stormwater Drainage Concept

A stormwater drainage concept has been prepared based the proposed architectural layout, road design and existing survey/contour information available. It consists of the following components:

- > Pit and piped drainage for Geraghty Street
- Internal road pit and pipework for the retirement village area
- > Vegetated swale drainage for the southern end of the retirement village
- > Vegetated swale drainage for the western properties adjacent to the turpentine forest
- > Water quality treatment using raingardens/bio-retention for individual properties and isolated parking areas
- > Two on site detention and water quality basins at the eastern end of the property adjacent to Cookson's Creek outside the 100 year flood extents
- Internal road pit and pipework for the RACF /independent living area (as referred to in the layout plans provided by architects) including raingardens for water quality treatment
- > Gross pollutant traps at the south east and south west corners of the development

The internal site drainage discharges mainly to the two basins which outlet to Cookson's Creek. Geraghty Street, Western residences, and the lower southern portion of for the RACF independent living area discharges to Tramway Creek. A small portion of the proposed residences along the northwest corner of the property discharge to Wilkies Street and outlet to the kerb and gutter. **Figure 5-1** illustrates the stormwater drainage arrangement.


The concept shown by GHD Anglican Retirement Villages - Surface Water Management Report – May 2006 stormwater management plan differs to the proposal submitted by Cardo. Main differences are:

- > Only one water quality basin nominated centrally near Cookson's Creek (in the flood plain).
- > The previous proposal does not take into account the natural contours of the site or adjacent roads.
- > The architectural and road layout has changed
- > A bridge no longer connects the two sides of the development
- > Overland flow directions have been confirmed by ground survey
- Water quality requirements are still the same as per the GHD report but rainwater tanks overflow to a raingarden where possible before connecting into the piped system

In general, the drainage concept is consistent with the concept proposed by GHD and has been updated to reflect the latest updates to the proposed development layout.



Figure 5-1 Drainage Concept Plan





6 Conclusion

The current study can be concluded as follows:

- The current study has been undertaken for Anglicare to support their concept plan modification application for an aged care facility in Bulli, NSW.
- > A WBNM model was developed to determine the flow hydrographs for the study catchment.
- > A two-dimensional TUFLOW model was developed to predict the flood behaviour on the site.
- The runoff from the Cookson's Creek catchment is predicted to overtop the railway and then flood the Geragthy Street and the site in pre-development scenario in a 100 year ARI design event and PMF. Tramway Creek is anticipated to overtop the rail in pre-development scenario in 100 year ARI design event and flood the site.
- The proposed development scenario raises the site levels to PMF, incorporates a sound barrier wall along the western boundary of the site and proposes replacement of the culvert under the Geragthy Street due to constraints imposed by the proposed development layout. The proposed development is predicted to result in a development which is above the PMF flood levels.
- Increases in MWSE of up to 1m are predicted against the proposed sound barrier wall and within the rail corridor. However, this increase is limited to the drain area and no impacts on the rail formation or closure time of the track is predicted. No impacts are predicted elsewhere as a result of the proposed development in the flood events up to and including PMF.
- A concept drainage has been prepared based on the updated layout (refer to Figure 5-1 for a copy of the concept drainage plan). In general, the drainage concept has been prepared consistent with the approved concept previously proposed by GHD with updates to reflect the changes to the development layout and taking into the account the site constraints.

APPENDIX



WBNM INPUT PARAMETERS



2. Catchment Details



Steps 2.1 to 2.4: Enter Data for each Subarea in the Model, including Topology, Surface and Flowpath Blocks and Loss Details

Catchment Statistics

Total Area [ha] 289.5

Total Impervious Percent [%] 18.3

No. of Subareas 41

No. of Subareas with WC Factor 41

Lag Parameters **Flowpaths Catchment Details** Rainfall Losses Continuing Loss Rate Populate Populate Populate **Routing Options** Sort Subareas Import Mid/Mif 1.29 0.1 R 0 1 0 2.5 0 Subarea Name D/S Subarea CG Coords (MGA) Outlet Coords (MGA) Area Imp Fraction Value CLR Imp Lag Imp IL Ε Ν Ε ha Ν % mm/hr mm mm SC27 SC26 21.72 0 0 0 0 1.29 0.1 R 2.5 0 1 1 0 SC26 SC25 R 15.35 0 0 0 0 1 1.29 0.1 1 0 2.5 0 SC25 SC24 0 13.82 0 0 0 0 1 1.29 0.1 R 1 0 2.5 SC24 SC21 4.58 0 0 0 0 24 1.29 0.1 R 1 0 2.5 0 SC23 SC21 6.23 0 0 0 0 19 1.29 0.1 R 1 0 2.5 0 SC21 SC20 2.37 0 0 0 37 1.29 R 0 2.5 0 0 0.1 1 SC22 SC20 2.66 0 0 0 0 70 1.29 0.1 R 1 0 2.5 0 SC20 SC28 0 R 5.59 0 0 0 60 1.29 0.1 1 0 2.5 0 SC28 R SC5 2.89 0 0 0 0 46 1.29 0.1 0 2.5 0 1 SC19 SC16 20.96 0 0 0 0 1.29 R 0 2.5 0 0.1 1 1 SC18 SC16 R 0 2.5 0 6.91 0 0 0 0 1.29 1 0.1 1 SC16 SC15 R 4.13 0 0 0 0 1 1.29 0.1 1 0 2.5 0 SC17 R SC15 0 0 0 0 3.38 0 0 1 1.29 0.1 1 2.5 SC15 SC12 0 0 R 0 4.24 0 0 1.29 0.1 2.5 0 1

SC14	SC13	22.31	0	0	0	0	1	1.29	0.1	R	1	0	2.5	0
SC13	SC12	3.79	0	0	0	0	1	1.29	0.1	R	1	0	2.5	0
SC12	SC11	20.8	0	0	0	0	17	1.29	0.1	R	1	0	2.5	0
SC11	SC10	18.73	0	0	0	0	3	1.29	0.1	R	1	0	2.5	0
SC10	SC9	7.79	0	0	0	0	5	1.29	0.1	R	1	0	2.5	0
SC9	SC5	3.02	0	0	0	0	38	1.29	0.1	R	1	0	2.5	0
SC5	SC3	2.25	0	0	0	0	1	1.29	0.1	R	1	0	2.5	0
SC6	SC4	4.77	0	0	0	0	2	1.29	0.1	R	1	0	2.5	0
SC4	SC3	6.96	0	0	0	0	7	1.29	0.1	R	1	0	2.5	0
SC3	SC1	2.25	0	0	0	0	45	1.29	0.1	R	1	0	2.5	0
SC8	SC7	7.51	0	0	0	0	13	1.29	0.1	R	1	0	2.5	0
SC7	SC2	6.68	0	0	0	0	70	1.29	0.1	R	1	0	2.5	0
SC2	SC1	12.24	0	0	0	0	40	1.29	0.1	R	1	0	2.5	0
SC1	dummy1	8.58	0	0	0	0	41	1.29	0.1	R	1	0	2.5	0
•														

TC7	TC4	5.27	0	0	0	0	50	1.29	0.1	R	1	0	2.5	
TC6	TC4	2.91	0	0	0	0	58	1.29	0.1	R	1	0	2.5	
TC5	TC4	2.18	0	0	0	0	70	1.29	0.1	R	1	0	2.5	
TC8	TC4	0.54	0	0	0	0	31	1.29	0.1	R	1	0	2.5	
TC9	TC4	2.7	0	0	0	0	70	1.29	0.1	R	1	0	2.5	
TC4	TC3	6.96	0	0	0	0	60	1.29	0.1	R	1	0	2.5	
TC3	TC1	12.15	0	0	0	0	51	1.29	0.1	R	1	0	2.5	
TC10	TC1	2.29	0	0	0	0	50	1.29	0.1	R	1	0	2.5	
TC2	TC1	2.31	0	0	0	0	5	1.29	0.1	R	1	0	2.5	
TC1	dummy2	9.68	0	0	0	0	13	1.29	0.1	R	1	0	2.5	
dummy1	dummy3	0	0	0	0	0	0	1.29	0.1	R	1	0	2.5	
dummy2	dummy3	0	0	0	0	0	0	1.29	0.1	R	1	0	2.5	
dummy3	SINK	0	0	0	0	0	0	1.29	0.1	R	1	0	2.5	

APPENDIX

B

WBNM RESULTS



View Results in Tabular Format

Results for Runfile: N:\Oran Park\Projects\FY18\138_Anglicare Bulli Redevelopment\Des-An\Hydrology\WBNM\temp03_Meta.out
6.1 Results

sults View I	Results at L	_ocation:	Stream Top	0	-	Flowrates		Volumes	Time to Peaks	Structures
Storm No.	1	2	3	4	5	6 7	8	9 10	11 12	13 14
ARI	100	100	PMF	PMF				, , , , , , , , , , , , , , , , , , , ,	1.1	10 14
Duration	90	120	30	60						
Catchment Area	289.5	289.5	289.5	289.5						
Impervious percent (%) Rainfall Depth (mm)	18.3 139.51	18.3 159.33	18.3 221.41	18.3 325.22						
Excess Rainfall (mm) Runoff Depth (mm)	136.45 133.07	155.24 149.22	220.39 218.71	323.18 320.42						
Time to Rain Peak (mins)	30	35	10	10						
VOLUMES at Outlet [m3]										
SC27	29225	33044	47676	69857						
SC26 SC25	49710 67987	56083 76546	81305 111497	119115 163336						
SC24 SC23	73977 8495	83204 9648	121475 13726	177928 20138						
SC21	85522	96205	140334	205562						
SC22 SC20	3680 96531	4197 108531	5879 158377	8631 231992						
SC28 SC19	100206 28214	112550 31905	164604 46016	241089 67427						
SC18	9366	10619	15196	22295						
SC16 SC17	43101 4587	48726 5206	70262 7444	102987 10912						
SC15	53335	60254	86986	127506						
SC14 SC13	30010 35072	33928 39620	48971 57277	71749 83919						
SC12 SC11	115938 140208	130628 157497	189708 230413	277988 337493						
SC10	150009	168168	247186	361994						
SC9 SC5	153652 256279	172035 286985	253593 422822	371344 619143						
SC6	6473	7344	10500	15401						
SC4 SC3	15909 274595	18028 307388	25807 453236	37860 663689						
SC8 SC7	10216 19440	11596 22081	16531 31287	24256 45919						
SC2	36153	41006	58238	85480						
SC1 TC7	320807 7253	358929 8257	529530 11637	775481 17077						
TC6	4013	4574	6427	9434						
TC5 TC8	3016 739	3440 841	4818 1190	7073 1746						
TC9 TC4	3735 28360	4260 32288	5967 45419	8761 66680						
TC3	45038	51192	72221	106040						
TC10 TC2	3151 3141	3590 3565	5055 5087	7419 7461						
TC1	64418	73052	103628	152127						
dummy1 dummy2	320807 64418	358929 73052	529530 103628	775481 152127						
dummy3	385224	431982	633158	927608						
PEAK FLOWRATES [m3/s]										
PEAK Stream Top SC27	0	0	0	0						
SC26 SC25	10.083 13.857	10.005 14.52	23.68 36.839	21.675 36.25						
SC24	17.431	18.122	46.955	48.704						
SC23 SC21	0 20.498	0 21.277	0 55.512	0 58.581						
SC22	0 21.661	0 22.508	0 58.741	0 62.932						
SC20 SC28	22.75	23.443	61.182	67.311						
SC19 SC18	0 0	0 0	0 0	0 0						
SC16	13.816	13.536	31.738	28.39						
SC17 SC15	0 16.009	0 16.468	0 39.988	0 36.285						
SC14 SC13	0 10.295	0 10.224	0 24.21	0 22.218						
SC12	27.765	28.795	71.546	66.632						
SC11 SC10	30.97 34.327	31.92 35.215	83.157 91.456	84.581 99.594						
SC9	35.609 58.818	36.717 60.685	93.484 154.596	105.674 177.052						
SC5 SC6	0	0	0	0						
SC4 SC3	2.947 62.314	2.753 64.313	6.271 163.271	5.429 188.938						
SC8	0	0	0	0						
SC7 SC2	4.628 8.268	4.262 7.814	9.641 17.865	8.415 15.696						
SC1	69.736 0	72.088 0	183.002 0	214.224 0						
TC7 TC6	0	0	0	0						
TC5 TC8	0	0 0	0	0						
TC9	0	0	0	0						
TC4 TC3	10.574 12.931	9.85 12.589	20.866 28.831	16.903 24.453						
TC10	0	0	0	0						
TC2 TC1	0 20.534	0 20.073	0 47.622	0 41.795						
dummy1 dummy2	71.144 21.404	73.694 22.07	182.698 55.236	218.689 50.872						
dummy3	85.013	87.745	225.175	263.053						
PEAK Stream Bottom SC27	0	0	0	0						
SC26	7.762	8.104	20.773	20.943						
SC25	12.621	13.076								

SC24 SC23	17.127 0	17.726 0	45.856 0	48.378 0
SC21	20.354	21.089	54.771	58.361
SC22 SC20	0 21.38	0 22.07	0 57.385	0 62.446
SC28	22.63	23.314	60.722	67.133
SC19 SC18	0 0	0 0	0 0	0 0
SC16	12.075	12.469	30.58	28.234
SC17 SC15	0 15.06	0 15.611	0 38.903	0 36.11
SC14	0	0	0	0
SC13 SC12	9.09 24.078	9.432 24.966	23.299 64.249	22.112 64.514
SC11	28.815	29.658	76.594	82.419
SC10 SC9	33.65 35.45	34.66 36.566	88.683 92.648	98.809 105.239
SC5	58.719 0	60.581 0	153.849 0	176.608 0
SC6 SC4	2.2	2.269	5.655	5.143
SC3 SC8	62.212 0	64.223 0	162.569 0	188.488 0
SC7	3.526	3.625	8.941	8.068
SC2 SC1	6.108 69.277	6.337 71.671	15.864 179.457	14.873 212.208
TC7	0	0	0	0
TC6 TC5	0 0	0 0	0	0 0
TC8	0	0	0	0
TC9 TC4	0 8.116	0 8.151	0 18.973	0 16.145
TC3	10.216	10.487	25.948	23.057
TC10 TC2	0 0	0 0	0	0
TC1	17.121	17.657	44.304	40.646
dummy1	71.144	73.694	182.698	218.689
dummy2 dummy3	21.404 85.013	22.07 87.745	55.236 225.175	50.872 263.053
PEAK Local Perv SC27	9.891	9.865	23.395	21.455
SC26	7.543	7.431	17.492	15.636
SC25 SC24	6.941 2.221	6.811 2.063	15.983 4.732	14.197 4.033
SC23	3.054	2.884	6.546	5.717
SC21 SC22	1.053 0.597	0.949 0.547	2.178 1.206	1.822 0.992
SC20	1.508	1.373	3.173	2.675
SC28 SC19	1.096 9.623	0.986 9.586	2.271 22.717	1.901 20.759
SC18	3.945	3.771	8.655	7.588
SC16 SC17	2.552 2.146	2.387 1.99	5.453 4.569	4.684 3.89
SC15	2.61	2.444	5.58	4.803
SC14 SC13	10.097 2.37	10.08 2.208	23.917 5.057	21.992 4.319
SC12	8.34	8.255	19.487	17.559
SC11 SC10	8.68 4.212	8.607 4.038	20.34 9.295	18.389 8.158
SC9	1.289	1.163	2.693	2.262
SC5 SC6	1.503 2.862	1.368 2.693	3.162 6.128	2.665 5.319
SC4	3.767	3.593	8.23	7.21
SC3 SC8	0.889 3.797	0.805 3.623	1.823 8.301	1.521 7.273
SC7	1.369	1.239	2.867	2.412
SC2 SC1	4.185 3.062	4.012 2.892	9.229 6.564	8.101 5.733
TC7	1.743	1.598	3.687	3.12
TC6 TC5	0.88 0.498	0.796 0.458	1.802 1.008	1.503 0.816
TC8	0.296	0.276	0.601	0.468
TC9 TC4	0.605 1.829	0.554 1.681	1.222 3.875	1.007 3.284
TC3	3.512	3.339	7.624	6.672
TC10 TC2	0.829 1.484	0.752 1.349	1.693 3.119	1.411 2.628
TC1 dummy1	4.687 0	4.516 0	10.437 0	9.179 0
dummy1 dummy2	0	0	0	0
dummy3 PEAK Local Imp	0	0	0	0
SC27	0.193	0.187	0.371	0.285
SC26 SC25	0.137 0.123	0.133 0.12	0.263 0.237	0.203 0.183
SC24	0.931	0.889	1.832	1.39
SC23 SC21	1 0.749	0.954 0.717	1.969 1.469	1.497 1.114
SC22	1.545	1.466	3.055	2.353
SC20 SC28	2.709 1.118	2.552 1.066	5.373 2.204	4.231 1.681
SC19	0.186	0.18	0.358	0.276
SC18 SC16	0.062 0.037	0.061 0.036	0.119 0.071	0.092 0.055
SC17	0.031	0.03	0.058	0.045
SC15 SC14	0.038 0.198	0.037 0.192	0.073 0.381	0.057 0.293
SC13	0.034 2.849	0.033 2.682	0.065 5.651	0.051 4.459
SC12 SC11	0.487	0.468	0.95	0.723
SC10 SC9	0.341 0.971	0.329 0.927	0.662 1.91	0.506 1.451
SC9 SC5	0.971	0.02	0.039	0.03
SC6 SC4	0.086 0.424	0.083 0.408	0.164 0.825	0.127 0.63
SC3	0.86	0.823	1.691	1.281
SC8 SC7	0.831 3.716	0.794 3.484	1.632 7.368	1.235 5.886
SC2	3.881	3.637	7.696	6.161
SC1 TC7	2.835 2.153	2.669 2.034	5.623 4.266	4.436 3.327
TC6	1.406	1.336	2.778	2.133

TC5 TC8 TC9 TC4 TC3 TC10 TC2 TC1 dummy1 dummy2 dummy3 PEAK Directed to Btm	1.277 0.149 1.567 3.337 4.852 0.969 0.103 1.061 0	1.215 0.145 1.487 3.134 4.531 0.925 0.101 1.012 0 0	2.52 0.287 3.099 6.62 9.61 1.906 0.198 2.09 0	1.929 0.221 2.388 5.261 7.782 1.448 0.153 1.591 0
SC27 SC26 SC25 SC24 SC23 SC21 SC22 SC20 SC28 SC19 SC18 SC16 SC17 SC15 SC14 SC13 SC12 SC11 SC10 SC9 SC5 SC6 SC4 SC3 SC8 SC7 SC2 SC1 TC7 TC6 TC5 TC8 TC9 TC4 TC3 TC10 TC2 TC1 dummy1 dummy2				
SC27 SC26 SC27 SC26 SC27 SC26 SC27 SC26 SC27 SC26 SC27 SC26 SC28 SC29 SC26 SC27 SC27 SC26 SC27 SC26 SC27 SC27 SC26 SC27 SC27 SC26 SC27	0 10.083 13.857 17.431 18.453 4.054 20.987 2.142 22.75 23.293 9.809 4.008 14.164 2.177 16.928 10.295 10.963 30.97 34.327 35.609 36.067 59.204 2.947 6.123 62.664 4.628 8.268 13.299 71.144 3.896 2.286 1.774 0.445 2.172 12.931 17.149 1.798 1.587 21.404 71.144 21.404 85.013 10.083 13.857 17.431 18.453 4.054 20.987 2.142 22.75 23.293 9.809 4.018 1.0295 10.295	0 10.005 14.52 18.122 19.07 3.661 21.751 2.013 23.443 23.967 9.721 3.815 14.6 2.011 17.552 10.224 11.345 31.92 35.215 36.717 37.249 61.102 2.753 6.049 64.725 4.262 7.814 13.1 73.694 13.582 2.133 1.673 0.421 2.041 12.589 17.17 1.677 1.424 22.07 87.745 10.005 14.52 18.122 19.07 3.661 21.751 2.013 23.443 23.967 9.721 3.815 14.6 2.011 17.552 10.224	23.68 36.839 46.955 49.452 8.349 56.597 4.26 61.182 62.47 22.992 8.745 35.674 4.62 43.805 24.21 27.824 83.157 91.456 93.484 93.624 154.845 6.271 14.397 163.186 9.641 17.865 30.876 182.698 7.703 4.531 3.528 0.888 4.321 28.831 41.441 3.563 3.293 55.236 225.175 23.68 36.839 46.955 49.452 8.695 49.452 8.695 49.452 8.6997 4.26 61.182 62.47 22.992 8.745 35.674 4.62 43.805 24.21	0 21.675 36.25 48.704 52.579 7.136 60.501 3.346 67.311 69.571 20.972 7.668 32.632 3.933 40.576 22.218 26.076 84.581 99.594 105.674 107.571 178.425 5.429 12.707 190.147 8.415 15.696 27.85 218.689 6.447 3.636 2.745 0.679 3.396 24.453 36.458 2.859 2.774 50.872 218.689 218.689 2

\$C13 \$C12 \$C11 \$C10 \$C29 \$C5 \$C6 \$C4 \$C3 \$C8 \$C7 \$C2 \$C1 \$C7 \$C2 \$C1 \$C5 \$C7	30.97 34.327 35.609 36.067 59.204 4.2.947 6.123 6.2664 4.628 8.268 13.299 71.144 3.896 2.286 1.774 0.445 2.172	11.345 31.92 35.215 36.717 37.249 61.102 2.753 6.049 64.725 4.262 7.814 13.1 73.694 3.582 2.133 1.673 0.421 2.041	27.824 83.157 91.456 93.484 93.624 154.845 6.271 14.397 163.186 9.641 17.865 30.876 182.698 7.703 4.531 3.528 0.888 4.321	26.076 84.581 99.594 105.674 107.571 178.425 5.429 12.707 190.147 8.415 27.85 218.689 6.447 3.636 2.745 0.679 3.396
TC4 TC3 TC10 TC2 TC1 dummy1 dummy2 dummy3 TIME to Peaks [mins]	17.149 1.798 1.587 21.404 71.144 21.404 85.013	12.589 17.17 1.677 1.424 22.07 73.694 22.07 87.745	28.831 41.441 3.563 3.293 55.236 182.698 55.236 225.175	24.453 36.458 2.859 2.774 50.872 218.689 50.872 263.053
TIME Stream Top SC27		0	0	0
SC26	30	40	20	35
SC25 SC24	40	43 46	25 25	35 40
SC23 SC21	0	0 45	0 25	0 40
SC22	0	0	0	0
SC20 SC28		46 49	26 28	40 42
SC19	0	0	0	0
SC18	30	40	20	30
SC17 SC15		0 41	0 20	0 30
SC14	0	0	0 20	0 35
SC13	34	43	22	34
SC11 SC10		48 53	25 30	39 43
SC9	49	58	31	45
SC5		59 0	31 0	45 0
SC4		40 60	15 32	25 45
SC8	0	0	0	0
SC7		40 40	15 20	25 25
SC1		60 0	31 0	45 0
TC6	0	0	0	0
TC5		0	0	0
TC9		0 35	0 10	0 20
TC3	30	40	16	21
TC10		0 0	0 0	0
TC1 dummy1		40 63	20 33	25 47
dummy2	33	42	22	31
dummy3 TIME Stream Bottom		58	30	45
SC27 SC26		0 47	0 27	0 40
SC25 SC24	44	51 51	29 29	42 42
SC23	0	0	0	0
SC21 SC22		49 0	28 0	41 0
SC20 SC28	45	51 52	30 30	43 44
SC19	0	0	0	0
SC18 SC16		0 42	0 22	0 34
SC17	0	0 45	0	0 35
SC15 SC14	0	0	0	0
SC13 SC12		43 50	23 29	36 41
SC11	48	55	32	45
SC10 SC9		58 60	33 33	46 46
SC5 SC6	52	60	33	46 0
SC4	34	43	22	31
SC3 SC8		61 0	33 0	47 0
SC7	33	42	22	30
SC2 SC1	55	44 63	24 34	35 48
TC7	0	0 0	0 0	0
TC5	0	0	0	0
TC8		0 0	0	0
TC4	31	41	17	23
TC3		44 0	22 0	29 0
TC2	0	0 44	0 24	0 32
dummy1	55	63 42	33	47
dummy2			22	31

dummy3	48	58	30	45
TIME Local Perv SC27	30	40	20	35
SC26	30	40	20	30
SC25 SC24	30 30	40 40	20 15	30 20
SC23	30	40	15	25
SC21	30 30	35 35	15 10	20 20
SC22 SC20	30	40	15	20
SC28	30	35	15	20
SC19 SC18	30 30	40 40	20 20	35 25
SC16	30	40	15	25
SC17	30	40	15	20
SC15 SC14	30 30	40 40	15 20	25 35
SC13	30	40	15	20
SC12	30	40 40	20 20	30 30
SC11 SC10	30 30	40	20	25
SC9	30	40	15	20
SC5 SC6	30 30	40 40	15 15	20 25
SC4	30	40	20	25
SC3	30	35	15	20
SC8 SC7	30 30	40 40	20 15	25 20
SC2	30	40	20	25
SC1 TC7	30 30	40 40	20 15	25 20
TC6	30	35	15	20
TC5	30	35	10	20
TC8 TC9	30 30	35 35	10 10	20 20
TC4	30	40	15	20
TC3	30	40 35	20 15	25 20
TC10 TC2	30 30	35 40	15	20
TC1	30	40	20	25
dummy1 dummy2	0 0	0 0	0 0	0 0
dummy3	0	0	0	0
TIME Local Imp	20	25	40	40
SC27 SC26	30 30	35 35	10 10	10 10
SC25	30	35	10	10
SC24 SC23	30 30	35 35	10 10	20 20
SC23	30	35	10	10
SC22	30	35	10	20
SC20 SC28	30 30	35 35	10 10	20 20
SC19	30	35	10	10
SC18	30 30	35 35	10 10	10 10
SC16 SC17	30	35	10	10
SC15	30	35	10	10
SC14 SC13	30 30	35 35	10 10	10 10
SC12	30	35	10	20
SC11	30	35	10	10
SC10 SC9	30 30	35 35	10 10	10 20
SC5	30	35	10	10
SC6 SC4	30 30	35 35	10 10	10 10
SC3	30	35	10	20
SC8	30	35	10	10
SC7 SC2	30 30	35 35	10 10	20 20
SC1	30	35	10	20
TC7 TC6	30 30	35 35	10 10	20 20
TC5	30	35	10	20
TC8	30	35	10	10
TC9 TC4	30 30	35 35	10 10	20 20
TC3	30	35	10	20
TC10 TC2	30 30	35 35	10 10	20 10
TC1	30	35	10	20
dummy1	0 0	0 0	0	0 0
dummy2 dummy3	0	0	0 0	0
TIME Directed to Btm				
SC27 SC26	0 0	0 0	0 0	0 0
SC25	0	0	0	0
SC24	0	0 0	0	0
SC23 SC21	0 0	0	0 0	0 0
SC22	0	0	0	0
SC20 SC28	0 0	0 0	0 0	0 0
SC28 SC19	0	0	0	0
SC18	0	0	0	0
SC16 SC17	0 0	0 0	0 0	0 0
SC15	0	0	0	0
SC14 SC13	0 0	0 0	0 0	0 0
SC13 SC12	0	0	0	0
SC11	0	0	0	0
SC10 SC9	0 0	0 0	0 0	0 0
SC5	0	0	0	0
SC6	0	0	0	0
SC4 SC3	0 0	0 0	0 0	0 0
SC8	0	Ō	0	0

SC7 SC2	0 0	0 0	0 0	0 0	
SC1	0	0	0	0	
TC7	0	0	0	0	
TC6	0	0	0	0	
TC5	0	0	0	0	
TC8	0	0	0	0	
TC9	0	0	0	0	
TC4	0 0	0 0	0 0	0 0	
TC3 TC10	0	0	0	0	
TC2	0	0	0	0	
TC1	0	0	0	0	
dummy1	0	0	0	0	
dummy2	0	0	0	0	
dummy3	0	0	0	0	
TIME OUTLET Inflow SC27	30	40	20	35	
SC26	34	43	25	35	
SC25	40	46	25	40	
SC24	42	49	27	41	
SC23	30	40	15	20	
SC21	42	48	27	41	
SC22	30	35	10	20	
SC20	44 45	49 52	28 30	42 44	
SC28 SC19	30	40	20	35	
SC18	30	40	20	25	
SC16	32	41	21	32	
SC17	30	40	15	20	
SC15	35	44	23	34	
SC14	30	40	20	35	
SC13	33 40	42 48	22 25	35 39	
SC12 SC11	40 46	48 53	30	43	
SC10	49	58	31	45 45	
SC9	52	60	33	46	
SC5	52	60	33	46	
SC6	30	40	15	25	
SC4	30	40	20	26	
SC3	53	61	33	46	
SC8 SC7	30 30	40 40	15 20	25 25	
SC2	30	40	20	30	
SC1	55	63	33	47	
TC7	30	35	15	20	
TC6	30	35	10	20	
TC5	30	35	10	20	
TC8	30	35	10	20	
TC9 TC4	30 30	35 40	10 16	20 21	
TC3	30	40	20	26	
TC10	30	35	10	20	
TC2	30	35	15	20	
TC1	33	42	22	31	
dummy1	55	63	33	47	
dummy2	33	42 50	22	31 45	
dummy3 TIME OUTLET Outflow	48	58	30	45	
SC27	30	40	20	35	
SC26	34	43	25	35	
SC25	40	46	25	40	
SC24	42	49	27	41	
SC23	30	40	15	20	
SC21 SC22	42 30	48 35	27 10	41 20	
SC20	44	49	28	42	
SC28	45	52	30	44	
SC19	30	40	20	35	
SC18	30	40	20	25	
SC16	32	41	21	32	
SC17 SC15	30 35	40 44	15 23	20 34	
SC14	30	40	20	35	
SC13	33	42	22	35	
SC12	40	48	25	39	
SC11	46	53	30	43	
SC10	49	58	31	45	
SC9 SC5	52 52	60 60	33 33	46 46	
SC6	30	40	15	25	
SC4	30	40	20	26	
SC3	53	61	33	46	
SC8	30	40	15	25	
SC7	30	40	20	25	
SC2	30 55	40 63	20 33	30 47	
SC1 TC7	55 30	63 35	33 15	47 20	
TC6	30	35	10	20	
TC5	30	35	10	20	
TC8	30	35	10	20	
TC9	30	35	10	20	
TC4	30	40 40	16 20	21 26	
TC3 TC10	30 30	40 35	20 10	26 20	
TC2	30	35 35	15	20	
TC1	33	42	22	31	
dummy1	55	63	33	47	
dummy2	33	42	22	31	
dummy3	48	58	30	45	

APPENDIX

FLOOD RESULT MAPS







Pre-Development Flood Extent 1% AEP

PROPOSED AGED CARE FACILITY
AT BULLI, NSW

Legend

Site Boundary

----+ Railway (LPI)

—— 1m Flood Height Contour

Cadastre (DFSI-SS, 2018)

Flood Depth (m)

0 - 0.25

0.25 - 0.50

0.50 - 0.75


0.75 - 1.00

1.00 - 1.25

1.25 - 1.50

> 1.50

1:2,000 Scale at A3







Map Produced by Cardno NSW/ACT Pty Ltd (WOL)
Date: 2018-08-07 | Project: 82018138_02
Coordinate System: GDA 1994 MGA Zone 56
Map: 82018138-02-GS-005_Pre_FloodExtentAEP.mxd 02
Aerial imagery supplied by nearmap (May, 2018)





Pre-Development Flood Extent PMF

PROPOSED AGED CARE FACILITY AT BULLI, NSW

Legend

Site Boundary

----+ Railway (LPI)

— 1m Flood Height Contour

Cadastre (DFSI-SS, 2018)

Flood Depth (m)

0 - 0.25

0.25 - 0.50


0.50 - 0.75 0.75 - 1.00

1.00 - 1.25

1.25 - 1.50

> 1.50

1:2,000 Scale at A3







Map Produced by Cardno NSW/ACT Ply Ltd (WOL)
Date: 2018-08-07 | Project: 82018138_02
Coordinate System: GDA 1994 MGA Zone 56
Map: 82018138-02-GS-006_Pre_FloodExtentPMF.mxd 02 Aerial imagery supplied by nearmap (May, 2018)





Pre-Development Flood Velocity 1% **AEP**

PROPOSED AGED CARE FACILITY AT BULLI, NSW

Legend

Site Boundary

Velocity Vector

----- Railway (LPI)

Cadastre (DFSI-SS, 2018)

Flood Velocity (m/s)

0 - 1 1 - 2

2 - 3

> 3

1:2,000 Scale at A3







Map Produced by Cardno NSW/ACT Pty Ltd (WOL)
Date: 2018-08-07 | Project: 82018138_02
Coordinate System: GDA 1994 MGA Zone 56
Map: 82018138-02-GS-007_Pre_FloodVelocityAEP.mxd 02 Aerial imagery supplied by nearmap (May, 2018)





Pre-Development Flood Velocity PMF

PROPOSED AGED CARE FACILITY AT BULLI, NSW

Legend

Site Boundary

Velocity Vector

----- Railway (LPI)

Cadastre (DFSI-SS, 2018)

Flood Velocity (m/s)


0 - 1

1 - 2

2 - 3

> 3

1:2,000 Scale at A3







Map Produced by Cardno NSW/ACT Pty Ltd (WOL)
Date: 2018-08-07 | Project: 82018138_02
Coordinate System: GDA 1994 MGA Zone 56
Map: 82018138-02-GS-008_Pre_FloodVelocityPMF.mxd 02 Aerial imagery supplied by nearmap (May, 2018)





Post-Development Flood Extent 1% AEP

PROPOSED AGED CARE FACILITY
AT BULLI, NSW

Legend

Site Boundary

----+ Railway (LPI)

—— 1m Flood Height Contour

Cadastre (DFSI-SS, 2018)

Flood Depth (m)

0 - 0.25

0.25 - 0.50


0.50 - 0.75

0.75 - 1.00 1.00 - 1.25

1.25 - 1.50

> 1.50

1:2,000 Scale at A3







Map Produced by Cardno NSW/ACT Pty Ltd (WOL)
Date: 2018-08-07 | Project: 82018138_02
Coordinate System: GDA 1994 MGA Zone 56
Map: 82018138-02-GS-009_Post_FloodExtentAEP.mxd 02
Agrial Imagency sumplied by pagarage (May, 2018)





Post-Development Flood Extent PMF

PROPOSED AGED CARE FACILITY
AT BULLI, NSW

Legend

Site Boundary

----+ Railway (LPI)

— 1m Flood Height Contour

Cadastre (DFSI-SS, 2018)

Flood Depth (m)

0 - 0.25

0.25 - 0.50

0.50 - 0.75


0.75 - 1.00

1.00 - 1.25

1.25 - 1.50

> 1.50

1:2,000 Scale at A3







Map Produced by Cardno NSW/ACT Pty Ltd (WOL)
Date: 2018-08-07 | Project: 82018138_02
Coordinate System: GDA 1994 MGA Zone 56
Map: 82018138-02-GS-010_Post_FloodExtentPMF.mxd 02
April Imageny: supplied by pagarage (May, 2018)





Post-Development Flood Velocity 1% **AEP**

PROPOSED AGED CARE FACILITY AT BULLI, NSW

Legend

Site Boundary

Velocity Vector

----- Railway (LPI)

Cadastre (DFSI-SS, 2018)


Flood Velocity (m/s)

0 - 1 1 - 2

2 - 3

> 3

1:2,000 Scale at A3







Map Produced by Cardno NSW/ACT Pty Ltd (WOL)
Date: 2018-08-07 | Project: 82018138_02
Coordinate System: GDA 1994 MGA Zone 56
Map: 82018138-02-GS-011_Post_FloodVelocityAEP.mxd 02 Aerial imagery supplied by nearmap (May, 2018)





Post-Development Flood Velocity PMF

PROPOSED AGED CARE FACILITY AT BULLI, NSW

Legend

Site Boundary

Velocity Vector

----- Railway (LPI)

Cadastre (DFSI-SS, 2018)

Flood Velocity (m/s)


0 - 1

1 - 2

2 - 3

> 3

1:2,000 Scale at A3







Map Produced by Cardno NSW/ACT Pty Ltd (WOL)
Date: 2018-08-07 | Project: 82018138_02
Coordinate System: GDA 1994 MGA Zone 56
Map: 82018138-02-GS-012_Post_FloodVelocityPMF.mxd 02 Aerial imagery supplied by nearmap (May, 2018)





Flood Impacts 1% AEP

PROPOSED AGED CARE FACILITY
AT BULLI, NSW

Legend

Site Boundary

----+ Railway (LPI)

Cadastre (DFSI-SS, 2018)

Change in Flood Levels (m)

Was Wet Now Dry

was wet now b

< -0.1

-0.1 to -0.05

-0.05 to -0.02

-0.02 to 0.02


0.02 to 0.05

0.05 to 0.1

> 0.1

Was Dry Now Wet

1:2,000 Scale at A3







Map Produced by Cardno NSW/ACT Pty Ltd (WOL)
Date: 2018-08-07 | Project:82018138_02
Coordinate System: GDA 1994 MGA Zone 56
Map: 82018138-02-GS-013_Post_FloodImpactsAEP.mxd 02
Aerial imagery supplied by nearmap (May, 2018)





Flood Impacts PMF

PROPOSED AGED CARE FACILITY
AT BULLI, NSW

Legend

Site Boundary

----+ Railway (LPI)

Cadastre (DFSI-SS, 2018)

Change in Flood Levels (m)

Was Wet Now Dry

____ was well now big

< -0.1

-0.1 to -0.05

-0.05 to -0.02

-0.02 to 0.02


0.02 to 0.05

0.05 to 0.1

> 0.1

Was Dry Now Wet

1:2,000 Scale at A3







Map Produced by Cardno NSW/ACT Pty Ltd (WOL)
Date: 2018-08-07 | Project: 82018138_02
Coordinate System: GDA 1994 MGA Zone 56
Map: 82018138-02-GS-014_Post_FloodImpactsPMF.mxd 02
Aerial imagery supplied by nearmap (May, 2018)

APPENDIX

SITE SURVEY



