## SMEC TESTING SERVICES Pty Ltd

Phone (02) 9756 2166, Fax (02) 9756 1137 E-Mail: smectesting@pacific.net.au

UNIT 14/1 COWPASTURE PLACE.

WETHERILL PARK, NSW 2164

## DYNAMIC CONE PENETROMETER TEST REPORT

PROJECT:

72 - 73 WEST PARADE, WEST RYDE

REPORT No: 05/1753

CLIENT:

**RESITECH AUSTRALIA** 

REPORT DATE: 22-02-05

PROJECT No:	10530/1376B				SHEET	1 of 1
TEST METHOD:A	S 1289.6.3.2		DATE TESTED: 18-02-05 TESTED BY: JK			
SITE No:	P1	P2	P3	P4		
LOCATION:	Refer to Drawing	Refer to Drawing	Refer to Drawing	Refer to Drawing		
	No. 05/1753	No. 05/1753	No. 05/1753	No. 05/1753		
STARTING	Surface	Surface	Surface	Surface		
LEVEL	Level	Level	Level	Level		
DEPTH (m)	Penetration Resistance (blows / 150mm)					
0.00-0.15	2	*	2	2		
0.15-0.30	5	2	4	2		
0.30-0.45	11	5	5	3	Tay to the tay of tay o	
0.45-0.60	10	8	6	10		
0.60-0.75	10	10	9	22		
0.75-0.90	12	11	10	R		
0.90-1.05	14	14	12			
1.05-1.20	14	22	11			
1.20-1.35	18	R	18			
1.35-1.50	22		22			
1.50-1.65	R		R		į.	
1.65-1.80						
1.80-1.95						
1.95-2.10		i				
2.10-2.25						
2.25-2.40						
2.40-2.55						
2.55-2.70						
2.70-2.85						
2.85-3.00						
3.00-3.15						
3.15-3.30						
3.30-3.45						
3.45-3.60						

REMARKS: \* Pre drilled prior to testing

3.60-3.75

APPROVED SIGNATORY .....

Laurie Ihnativ - Manager

NATA Accredited Laboratory

Number: 2750

The tests, calibrations or measurements covered by this document have been performed in accordance with NATA requirements which include the requirements of ISO/IEC 17025 and are traceable to Australian national standards of measurement. This document shall not be reproduced, except in full.

**REVISION 3**