

Civil Infrastructure Report Hinchinbrook Creek Bridge, Link Road and Signalised Intersection Former Hoxton Park Airport – Cowpasture Road Hoxton Park

Prepared on behalf of the Mirvac Projects Pty Limited For Submission to the Minister for Planning

September 2010

ADW JOHNSON PTY LIMITED SURVEYING ENGINEERING AND TOWN PLANNING CONSULTANTS

ABN 62 129 445 398

central coast

2 bounty close, tuggerah nsw 2259 po box 3717, tuggerah nsw 2259

ph. 02 4305 4300 fax. 02 4305 4399 video. 02 43054374

email. <u>coast@adwjohnson.com.au</u>

hunter region

7/335 hillsborough road, warners bay nsw 2282

ph. 02 4978 5100 fax. 02 4978 5199 video. 02 4954 3948

email. <u>hunter@adwjohnson.com.au</u>



Document Control Sheet

Issue	Amendment	Date	Prepared by	Checked by
Α	Issued for inclusion in EAR	15/09/2010	HW	PJ



Executive Summary

ADW Johnson have been engaged to prepare a Civil Infrastructure Report to accompany a Section 75W modification to Concept Plan Approval 10_0007 and stage 1 infrastructure approval 10_0008 for the Hoxton Park Warehouse project. This modification is required to allow for the construction of a link road, bridge and culvert bank and signalised intersection onto Cowpasture Road providing a second access point onto Cowpasture road from current development under construction and the future residential precinct to the north. This connection is required under a Voluntary Planning Agreement made between Mirvac and Liverpool City Council.

The proposed link consists or;

- Localised filling to construct abutments;
- A 72m span reinforced concrete bridge;
- A 10 cell 4.2m span culvert bank;
- Associated services; and
- A signalised intersection onto Cowpasture Road.

The following report documents concept design arrangements of the infrastructure in order to allow for assessment of the proposal by the Department of Planning.

Concept design drawings have been prepared by ADW Johnson and are attached demonstrating the overall proposal.

A concept design report was prepared by Cardno and is attached indicating the general features of the bridge.

Consultation has occurred with the RTA and the RTA has agreed in principle to the arrangement of the intersection with Cowpasture Road. Concurrence of the RTA is required for the intersection as Cowpasture Road is a Classified Road and the proposed intersection is signalised. The RTA has also agreed to the alignment of the link road. The traffic impacts of this arrangement have been dealt with by Colsten Budd Hunt and Kafes and are found to be satisfactory.

A flooding Impact Assessment was prepared by Golder Associates for the construction of the proposal on the floodplain hydraulic of Hinchinbrook Creek. Whilst some afflux occurred, it was localised to the bridge area which is to be expected. There was no modelled increase in flooding levels in the vicinity of any existing residential areas and the flood free status of Cowpasture Road was not compromised. Any afflux was wholly contained within the public lands forming Hinchinbrook Creek.



Table of Contents

1.0	BACK	GROUND4
	1.1	Introduction4
	1.2	Proposed Infrastructure
2.0	PROP	OSED INFRASTRUCTURE DESIGN
	2.1	Overall Proposed Infrastructure
	2.2	Proposed Hinchinbrook Creek Bridge5
	2.3	Proposed Culvert Bank5
	2.4	Proposed Link Road6
	2.5	Proposed Signalised Intersection onto Cowpasture Road6
	2.6	Impacts of Proposed on Flooding in Hinchinbrook Creek7
	2.7	Services required with Bridge and Link Road Crossing7
	2.8	Geotechnical Engineering
3.0	CONC	CLUSION 8

APPENDICES

Appendix A	Preliminary Civil Design Drawings
Appendix B	Cardno Bridge Concept Design Report
Appendix C	RTA Meeting Minutes, General Arrangements and In Principle Acceptance
	of Proposed Intersection Treatments



1.0 Background

1.1 Introduction

ADW Johnson have been commissioned by Mirvac Projects Pty Limited to prepare concept infrastructure design and report to accompany a Part 3A Project Application for the provision of the Hinchinbrook Creek bridge crossing, link road and signalised intersection onto Cowpasture Road.

The location of the proposed infrastructure is adjacent to the development of the former Hoxton Park Airport site and proposed future residential precincts to the north of the industrial development currently under construction.

Cowpasture Road is currently being upgraded by the RTA as part of the Cowpasture Road Design Alliance with practical completion of the contract expected before the end of 2010. The intersection proposed requires the reconfiguration of some works currently being undertaken and the provision of traffic control signals and associated works.

Previous studies have been prepared as part of the development of the former Hoxton Park Airport site have been extended to include the works proposed under this application.

1.2 Proposed Infrastructure

The infrastructure proposed under this application consists of;

- New concrete bridge spanning 72m across Hinchinbrook Creek;
- New culvert bank consisting of 10 cells of 4.2m span;
- Earthworks associated with the provision of the bridge abutments and filling over the culverts and creation of the link road;
- Construction of the link road;
- Construction of a new signal controlled intersection of the link road onto Cowpasture Road.



2.0 Proposed Infrastructure Design

2.1 Overall Proposed Infrastructure

As outlined in Section 1.2, the proposal seeks approval for the creation of the link road, bridge, culverts and intersection with Cowpasture Road. Preliminary civil design drawings are shown in Appendix A. An indicative erosion and sediment control plan is provided in the concept civil design drawings shown in Appendix A which will be refined as part of the detailed design development.

2.2 Proposed Hinchinbrook Creek Bridge

Cardno was engaged to prepare a concept design for the Application for submission with the Application to Department of Planning. This concept design report is shown in Appendix B. Whilst the detailed design is yet to be completed, at this stage a proprietary "M-Lock" system appears to be the most efficient type of construction. The structure comprises precast reinforced concrete headstocks supported on piles which support the precast bridge planks and pavement. The key bridge design parameters are;

- Six equal spans of 12 metres in length;
- 9.6m clear width between traffic barriers (2x3.5m lanes, 2x1.3m shoulders and 2.5m wide cycleway on the northern side;
- Pavement crossfalls are proposed two way at 3%;
- Traffic barriers F Type Regular Performance to RTA Specifications;
- Deck drainage is proposed to be by scuppers into the floodplain below;
- Bridge deck is proposed to be supported on 585mm diameter spun precast concrete piles with depth and set to be determined at the detailed design stage.

Hydraulic impacts of the proposed bridge structure on the Hinchinbrook Creek floodplain are discussed in Section 2.6.

2.3 Proposed Culvert Bank

In addition to the main channel conveyance bridge crossing, there is also a proposed bank of box culverts consisting of 10 cells of 4.2m span. These culverts assist in passing higher flood flows through the link road crossing and assist in minimising afflux both upstream and in the proximity of the adjoining "Bus Depot" site. The structural and final civil design of this culvert group will be determined at the detailed design stage along with scour protection requirements upstream and downstream of the culverts. Preliminary design drawings are presented in Appendix A.

Hydraulic impacts of the proposed bridge structure on the Hinchinbrook Creek floodplain are discussed in Section 2.6.



2.4 Proposed Link Road

The link road forms a central plank of the access arrangements for both the industrial development of the former Hoxton Park Airport site and proposed future residential precinct to the north. It connects the roundabout currently under construction at the former airport development and a signalised intersection with Cowpasture Road via both the aforementioned bridge and culverts.

The configuration of the link road consists of two 4.5m travel lanes, kerb and gutter and a 2.5m concrete shared pathway linking the industrial and residential developments with Cowpasture Road to the east. The traffic engineering requirements for this link road have been assessed by Colsten Budd Hunt and Kafes in their report *Traffic Assessment For Northern Access To Hoxton Park Development – August 2010.*

.

2.5 Proposed Signalised Intersection onto Cowpasture Road

The link road is proposed to connect to the existing road network at a signalised intersection with Cowpasture Road. As noted above, Cowpasture Road is currently being upgraded by the RTA and works will be required to accommodate the proposed intersection. As Cowpasture Road is a Classified Road under the Roads Act and as the works involve traffic signals, RTA concurrence to the design and works is required.

A general arrangements design of the intersection was prepared by ADW Johnson and consultation occurred with the RTA. RTA have provided in principle agreement to the proposal. The submitted drawing and email confirmation of acceptance from the RTA is shown in Appendix C along with the minutes of the pre design meeting held with council and the RTA.

The drawings shown in Appendix A generally reflect what was submitted to the RTA in terms of the general configuration, lane lengths and traffic facilities with the geometry improved more in keeping with the detailed design requirements of the RTA Road Design Guide. The design will be compliant with relevant RTA and Council standards and specifications including the RTA Road Design Guide, AUSTROADS Pavement Design Guide, and the latest version of Australian Standard AS5100.

The general configuration of the intersection includes;

- Left turn storage lane from Cowpasture Road into the link road minimum 30m long (excluding taper);
- Right turn storage from Cowpasture Road into the link road minimum 150m long (excluding taper);
- Two right turn lanes out of the link road onto Cowpasture Road minimum 50m long (excluding taper);
- Signalised slip lane for left out movements from the link road onto Cowpasture Road minimum 50m long (excluding taper).

In consultation with the RTA, marked footways have been provided on the south bound approach and across the link road to cater for pedestrians and cyclists. Marked footways have not been provided on the northbound approach however provision for future upgrade to mark footways on



this approach will be made in the design.

The proposed geometry of the intersection was modelled and confirmed appropriate in SIDRA by Colsten Budd Hunt and Kafes.

2.6 Impacts of Proposed on Flooding in Hinchinbrook Creek

Golder Associates were engaged to update the 2 dimensional TUFLOW model used for the floodplain assessment for the industrial Project Applications on the former airport site to include the proposed bridge, abutments, filling and culvert bank. This report is titled *Hinchinbrook Creek Link Road – Flood Impact Assessment Revision 2*.

The salient points from the analyses and reporting are;

- The proposed bridge is flood free in the 1:100 year ARI event
- After the introduction of the bridge, culverts and fill there is afflux both upstream and downstream of the bridge by virtue of the reduction in conveyance. This afflux is localised to the bridge area and there are no modelled flood increases in the vicinity of the residential area to the north of the site or to the south;
- The introduction of the bridge, culverts and fill does not impact on the flood free status of Cowpasture Road;
- There are some modelled velocity increases localised to the bridge and culverts structures that will be addressed as part of the detailed design.

2.7 Services required with Bridge and Link Road Crossing

As part of the development services may be required to be installed across the link road and bridge. Initial planning is currently being undertaken to determine the type and size of any required services. If required, these will be installed to authority requirements within the public road reserve.

2.8 Geotechnical Engineering

In relation to all of the proposed road work and bridgework elements, preliminary advice has been obtained from geotechnical engineers in relation to design parameters and construction methodologies to be adopted. As part of the detailed design development, any geotechnical advice and recommendations will be taken into account.



3.0 Conclusion

As part of the VPA negotiated between Mirvac and Liverpool City Council, a bridge and link road is required along with a signalised intersection to link the industrial development currently under construction with Cowpasture Road. Preliminary designs have been prepared for each of the elements to support the modification of the original consents to demonstrate the arrangement of the proposed infrastructure. Construction of the aforementioned infrastructure allows for a second controlled access onto Cowpasture Road as required by the RTA and the original consent and allows for the orderly development of the industrial and residential precincts in and around the former Hoxton Park Airport site.


As civil engineers we are in support of the application.

Appendix A

Preliminary Civil Design drawings

PROPOSED HINCHINBROOK LINK ROAD "FORMER HOXTON PARK AIF 1101 D.P. 1130459, LOT 404 D AND LOT 4051, D.P.1152 COWPASTURE ROAD HOXTON PARK





INDEX OF DRAWINGS

DRAWING	NAME
150133-DA-001 150133-DA-002	TITLE SHEET, LOCALITY PLAN AND INDEX OF DRAWINGS OVERALL SITE PLAN.
150133-DA-100 150133-DA-101	DETAIL PLAN - SHEET 1
150133-DA-102	· ⊢
150133-DA-103	BRIDGE ROAD - PLAN AND LONGITUDINAL SECTION
150133-DA-104 150133-DA-105	BRIDGE AND ROAD - I YPICAL SECTIONS INTERSECTION - VEHICLE SWEPT PATHS
150133-DA-200	EROSION AND SEDIMENT CONTROL PLAN




TITLE SHEET, LOCALITY PLAN AND INDEX OF DRAWINGS


DA


PROJECT No. 150133


DIAL 1100
BEFORE YOU DIG


30459, L)T 4051 ' PASTU OXTON	N\A A.H.D.	
PROPERTY DESCRIPTION LOT 101 D.P. 11 AND LC COW H	SURVEYED	
Central Coast 2 Bounty Close, P.O. Box 3717, Tuggerah N.S.W. 2259 Phone: (02) 4305 4300 Fax: (02) 4305 4399 email: coast@adwjohnson.com.au	www.adwjohnson.com.au ABN 62 129 445 398	
MOD M	ohnson	
		is — Hoxton Park Bridde Road/Urawings/ENG/130135_DA_001 Aidwa
W.M. H.W. M.A. P.J.		r bridge koa
		xton rar
W.W.		.OH - 50















LOT 101 D.P. 113 AND LOT COW | HC

)
130459, LOT 404 D.P. 1147551 OT 4051 D.P. 1152675	PLAN TITLE		
W PASTURE ROAD		BRID	
HOXTON PARK		TYPI	=
DATUM	PROJECT No.	DSIG	1%
A.H.D.	150133	1	ш

	NUMBER 104	
BRIDGE AND ROAD TYPICAL SECTIONS	I U	
BRIDGE / TYPICAL	DISCIPLINE	
	ı	





LOT 101 D.P. 1130459, LOT 404 D.P. 1147551 AND LOT 4051 D.P. 1152675 COW PASTURE ROAD HOXTON PARK PROPERTY DESCRIPTION

PLAN TITLE

SURVEYED

DATUM

A.H.D.

∀ | Z

PROJECT No. 150133

INTERSECTION VEHICLE SWEPT PATHS

PROJECT HINCHINBROOK CREEK LINK ROAD

SCIPLINE

REV.

[A]201_AQ_EE1021

M. G. A.

0000

0

0.20

26M

B-DOUBLE

4.30

12.50

8.40

3.00

9.40

0.00

8.30

1.40

0.30

6.00 22.20 70.00

..

Lock to Lock Time Steering Angle Articulating Angle

7.50

..

Tractor Width Trailer Width Tractor Track Trailer Track

... 2.50 ... 5.50 ... 35.2

Width Track Lock to Lock Time Steering Angle

 (\bigcirc)

-ROAD


6.60

BUS1 meters

12.50

100mm AT FULL SIZE

ohnson



Appendix B

Cardno bridge concept design report





Hoxton Park Concept Design Report

Prepared for ADW Johnson Project No. 607207

14 September 2010



Cardno (NSW/ACT) Pty Ltd

ABN 95 001 145 035 Level 3, 910 Pacific Highway Gordon NSW 2072

Telephone: 02-9496 7700 Facsimile: 02 9499 3902

International: +61 2 9496 7700 sydney@syd.cardno.com.au

www.cardno.com.au

Document Control

Version	Date	Author		Reviewer		
Rev 2	14 September 2010	Chin Cheah	MA	Colin Edmonds	169	
			- 1/	- 6	, , ,	

"© 2010 Cardno (NSW/ACT) Pty Ltd All Rights Reserved. Copyright in the whole and every part of this document belongs to Cardno (NSW/ACT) Pty Ltd and may not be used, sold, transferred, copied or reproduced in whole or in part in any manner or form or in or on any media to any person without the prior written consent of Cardno (NSW/ACT) Pty Ltd."

September 2010

Executive Summary

This report describes the concept design for the Bridge crossing Hinchinbrook Creek at Hoxton Park for ADW Johnson. The proposed bridge is to allow for two lanes traffic plus cycleway and allowance for utilities.

The report also provides suitable information for the lodgement as part of ADW Johnson's engineering report to the Department of Planning for the Part 3A application.

Table of Contents

Ε	xecut	ıtive Summary	ii			
1	In	ntroduction	4			
		Scope of Reports				
		Design Documentation				
		Design Features				
		ndicative Schedule of Materials				
	Indicative Schedule of Finished Treatment5					
	Construction Methodology5					
		Photograph of Similar Structures				

Annexes

Annex 1	Concept Design Drawing
Annex 2	RTA Document TB-DF062
Annex 3	Indicative Material Schedule
Annex 4	Indicative Finished Treatment Schedule
Annex 5	Construction Methodology
Annex 6	Photographs of Similar Structures

1 Introduction

Cardno has been engaged by ADW Johnson to undertake the design and documentation of M-Lock Bridge at Hoxton Park. The bridge is to provide a link from an industrial estate to Cowpasture Road at Hoxton Park.

Cardno's concept design drawing for the bridge is presented in Annexure 1.

1.1 Scope of Reports

This Concept Design Report for the Bridge over Hinchinbrook Creek incorporates the following:

- An outline of the design features;
- Schedule of Building Materials;
- Schedule of Finished Treatment;
- Construction Methodology;
- · Photograph of Similar Structures.

1.2 Design Documentation

This report consists of the following design documentation:

- This report;
- Annexure 1 Concept Design Drawing;
- Annexure 2 RTA Document TB-DF062;
- Annexure 3 Indicative Material Schedule;
- Annexure 4 Indicative Finished Treatment Schedule;
- Annexure 5 Construction Methodology;
- Annexure 6 Photographs of Similar Structures.

2 Design Features

The bridge comprises of 6 equal spans of 12 metres length. The width of the bridge shall provide 9.6 m clear width between traffic barriers, comprising 2/3.5 m traffic lanes 2/1.3 m shoulders and a 2.5 m cycleway on the northern side. The carriageway crossfall is 3% two-way. The bridge is located in a straight horizontal and vertical alignment with zero skew.

The bridge deck units are to be designed based on the Rocla M-Lock Bringing System for a Highway Bridges. The superstructure comprises 1200mm wide inverted U-shape reinforced concrete planks which are bolted down to the headstocks. The 2.5m cycleway has an in-situ reinforced concrete downstand integral with the precast planks.

The barriers on the traffic side are precast standard Type F Regular Performance Barrier. The barrier is connected to the bridge system via the transverse stressing that connects the deck units. A barrier with 1.3m height is provided at the edge of bridge deck adjacent to the cycleway and a post and rail are attached to the top of the regular performance barrier which is adjacent to the cycleway. Provision is made for ducts in the traffic barriers. Bridge drainage is via free draining scuppers located in the precast barriers.

Hoxton Park – Concept Design Report *ADW Johnson*

The substructure comprises precast reinforced concrete headstocks, with void included for the protruding precast pile reinforcement. The piles are 585mm diameter spun precast reinforced concrete piles, which are driven into the required depth and set.

Further details on the bridge inventory is summarised in Annexure 2 in the format of RTA Document TB-DF062.

3 Indicative Schedule of Materials

A list of indicative building materials covering all structural components has been attached in Annexure 3.

4 Indicative Schedule of Finished Treatment

A list of indicative finished treatment for all structural components has been attached in Annexure 4.

5 Construction Methodology

The construction sequence for the bridge has been nominated in 6 Stages as detailed in Annexure 5.

6 Photograph of Similar Structures

Several photographs of completed M-Lock Bridges that have similar features have been attached in Annexure 6.

Annex 1 Concept Design Drawing

Date Date Date Date CONCEPT PROPOSAL-SHEET 2

Somm ON A1 ORIGINAL BRIDGE OVER HINCHINBROOK CREEK
AT HOXTON PARK
HINCHINBROOK CREEK LINK ROAD
LIVERPOOL CITY COUNCIL

140

NOT FOR CONSTRUCTION

AS SHOWN

607207-0002

NOTES FOR NOTES REFER TO DRG 0001


Cardno

HW

© Cardno Ltd 2010

All Rights Reserved.

This document is produced by Cardno Ltd solly for the benefit of and use by the dient in accordance with the cerns of the retember. Cardno Ltd does are death and assure any responsibility of labelity whitsdood to any the pany artificial out of any use or retilence by third pany on the content of this document. ABN: 95 001 145 035 910 Pacific Highway, Gordon, NSW Australia 2072 Phone (+612) 9496 7700 Fax (+612) 9499 3902 Email: Sydney@kardno.com.au Web: www.cardno.com.au



Annex 2 RTA Document TB-DF062

Design Proposal

BRIDGE DESIGN PROPOSAL - SUMMARY AND APPROVALS

Project No: Sketch No: 607207-001 File No: Region: Liverpool Bridge No: Road No: Local Government Area: Liverpool City Council Project: Hoxton Park M-Lock Bridge REASON FOR NEW BRIDGE: Provide New Bridge Across Hinchinbrook Creek Bridge Over Hinchinbrook Creek **PROPOSED BRIDGE:** 6/12m Number and length of spans: Overall length: 72.75 m Bridge width: Between traffic barriers 9.61 Overall: 13.08 m m Number of footways: Width: 2.5 m Side: North Type of wearing surface: Asphalt Concrete Wearing Surface M-Lock Planks Superstructure: Substructure: Concrete Headstock on Precast Driven Piles for intermediate piers; Spill-through Abutments on Precast Driven Piles (TBC). Clearances: Dictated by Required Waterway Area. Special features and requirements: N/A

ALIGNMENT										
Horizontal alignment: Straight Bearing					0 6	"	Radius		N/A	m
Skew * No Skew		Crossfall	Crossfall 3% Two Direction		n					
Vertical Alignment	Grade	: 0%	Summit /	Summit / Sag Curve: * N/A						
RL Datum: AHD Coordina			Coordinat	ate Grid (MGA, ISG, Local):			ISG			
Chainages at end of deck: Abutment A				67.5 (Assumed) Abutment B		В	139.5 (Assumed)			
Levels at end of deck: Abutment A				42 Lin	.15 on Coi ie	ntrol	Abutment	В	42.15 on Cont	rol Line
Source of horizontal and vertical alignment information: (eg: Bridge Site Survey Drwg No, MX File etc)					Survey Dr	awing by	ADW Jonh	son		

ESTIMATED COST AN	D SIGN OFFS			
Estimated construction cos	st** = Deck area*** m2 @ estima	ated deck un	nit rate \$/m2	
	@ \$:	= \$	
	any allowances for design, super etween bottom faces of parapets			
Recommended	Approved			
Supervising Bridge Engineer (New Design)	Principal Bridge Engineer / Senior Bridge Engineer (New Design)	RTA Proj	ect Manager	Principal Bridge Engineer / Senior Bridge Engineer (New Design)
****Consultant's Rep	**** Consultant's Director			**** RTA Regional Mgr
Date:	Date:	Date:		Date:

^{****} Other than RTA Bridge Engineering in-house or managed designs

BRIDGE DESIGN PROPOSAL

Project No: Sketch No: 607207-001 File No:

EXISTING	BRIDGE N/A							
Drawing No:	:			Gene	ral File	No:		
Bridge No:					Constru	ıcted:		
Type of substructure	x.			Type	of structur	re:		
Width betwe	een parapets or kerbs:			m	Fo	otway	/s:	
Length:				m	Νι	ımber	of spans:	
Deck level F	RL:	Above H	.F.L.:	Yes / N	o Na	avigati	on Clearance:	
Condition (ir	ncl. any load rating):		'		'		'	
Proposed fu	ture use of existing bridg	je:						
Public Utility	Services (No off, size a	nd type):						
CLEARAN	CES							
Horizontal:	Actual				m fro	m		
	Required				m			
Vertical:	Actual				m abo	ove		
	Required				m			
APPROAC	HES							
Road Plans	No (or File No):							
Design Spec	ed:		50			km/ł	nr	
No of Lanes	:		2					
Median Wid	th:		3.5			m		
Shoulder Widths:			1.3			m		
Verge Width:			0		m			
Formation Width:			13.08			m		
AADT/ Day:			7500					
% of Comm	ercial Vehicles:		20			%		
Pavement ty	pe on approaches:		Aspha	alt wearing	surface			

OTB-TP-202-F62 Issue 11 (30 June 2008) Page 2 of 6

BRIDGE DESIGN PROPOSAL

Project No: Sketch No: 607207-001 File No:

WATERWAY														
WATERWAY REPORT No:			Т	ВС				Date:				TBC		
General Comments:	TBC													
Catchment Area:	TE	зС	km ²			Normal wate	r lev	el RL	TBC					
Is waterway navigable?	Yes / N	0 *	Is wate tidal?	erway	′	Yes / No *		MHWS RL			N	/ILWS RL		
Observed H.F.L.	RL			Date										
Flood Event Flood Le		od Leve	el RL		Disch	narg	e		Stream v	eloci	ty	Affl	ux	
			RL			m [°]	³ /s			m/se	ес		m	1
20 year ARI														
100 year ARI														
2000 year ARI														
D 101				Ι.										
Proposed Clearance	e:		m	ab	ove									
Estimated Depth of	Scour:				m	Scour protect	ctior	n require	d? T	o be dete	rmine	ed		
Estimated depth of	debris for d	debris	s loadir	ng:				m						
SUBSTRUCTURE	Ē											TBD indicat Determined	es To	Be
GEOTECHNICAL REPORT No:		TI	BC						Date	Date TBC				
Geotechnical inves	tigation co	mple	eted	TBC Further geotechr				otechnica	ıl inves	stigation re	equir	ed	TBC	
FOUNDATIONS		ı												
Founding material:		TB	С											
Type of foundations		Abı	utments	3:		585mm D	rive	n Spun F	Piles					
(Spread footings or	pile type)	Pie	rs:			585mm D	rive	n Spun F	Piles					
Allowable Bearing F	Pressure:	SLS	S / ULS	*	TBC	,			kPa	a				I
Maximum Pile Load	s:	SLS	S / ULS	S *	Abu	tment Piles	85	0/1350	kN	Pier F	Piles	1350/205	50	kN
Pile Contract Levels	S :		ut A RL		TBE			Abut	B RL	TBD				
		Pie	rs RL		TBD									
Basis for determinat Levels and type of for					rmine	rised from geo ed from modell ns								
Environmental Factor selecting type of four		ered	in	No disposal of spoil is required and minimises risk of spillages into creek										
(Report attached Yes														
OHS Factors considerable type of foundation:			ng	Minir	nises	in-situ work a	nd e	excavatio	ns					
(Report attached Ye	s/NO/N/	A ^)												

BRIDGE DESIGN PROPOSAL

Project No: Sketch No: 607207-001 File No:

\sim 1	$\overline{}$	\sim τ	 JCI		

Type of Superstructure:	12m Highway Ty	2m Highway Type M-Lock Planks with in-situ reinforced concrete slab								
No of Spans:	6	Span Lengths: 12								
Reason for Selection:	Minimises in-situ	Minimises in-situ work over creek								
OHS Factors considered (Report attached Yes / No			Minimises risk of accidents from falls at height							
Environmental factors co (Report attached Yes / N		on:		Minimises risk of spillages into the creek						

DESIGN LOADING	6 (As	sume	AS5	100 u	ınless state	d other	wise	:)						
Traffic loading			SM1600											
No of 3.2m wide design lanes:			3			SM160	00 lo	ading:		Yes				
Non Standard Truck loading:			N/A			Constr	uctio	on load	ding:	N/A				
Cycleway loading:			5kPa			Other	load	ing:		N/A				
Fatigue Load Effects:	ue Load Effects: No of heavy vehicles per lane per			er lane per d	ay:	ТЕ	3C		Route Fa	actor:	0.3			
Superimposed Dead L	oad:	AC v	wearing surface, Concrete barriers, Railings											
Temperature		Ran	ange: Shade Air Temp			45 to -5	45 to -5℃ Gradien t:		ien t:	Regi	ional Ca	ategory	y 18	${\mathfrak C}$
Design Wind Speed:			ULS		48 m/s		S	LS		3	37	m/s		
Differential Settlement	:	Т	TBC											
Mining Subsidence Pa	rameter	s: N	N/A											
Stream Flow Effects:		Т	TBC											
Impact Loads: Ship / Vehicle /				*	Part of the	structur	e:							
Earthquake Design Parameters:	Acceler coefficie		0.08	0.08 Importance factor				Site Factor		TBD	BEDO	DC TBD)
Other Loadings: N/A														

ARTICULATION									
Method of Resisting Long	itudinal Forces:	Fixed Restraint at Piers							
Method of Resisting Trans	sverse Forces:	Transverse Re	Transverse Restraint at Piers						
Longitudinal Movements Thermal (mm): Expansion		TBD	Thermal contraction	TBD	Creep and TBD shrinkage)			
Ultimate deck joint mover	nents: (+ve openin	g, -ve closing):	Opening (mm)	TBD	Closing (mm)	TBD			
Mining Subsidence: N//		Abutments inte	No						

	Deck Joints:		Bearings:				
Location	Туре	Location	Number	Туре			
Abutment(s)	AC Expansion Joint	Abutment(s)	10	Laminated Elastomeric			
		Pier(s)	2	Laminated Strips			

Bearing Replacement:	Provision made for jacking off substructure?	TBC	

BRIDGE DESIGN PROPOSAL

Project No: Sketch No: 607207-001 File No:

PROVISIONS FOR PUBLIC UTILITY SERVICES ON THE PROPOSED BRIDGE:

	Water	Sewer	Gas	Electricity	Telstra	Other
Number						
Size						
Side						

DRAINAGE:	Scuppers	
If no scuppers, i	s width of flow contained in shoulder?	
Piped storm wat	er under deck necessary	

LIGHTING:	N/A			
-----------	-----	--	--	--

BARRIER TYPES:									
Traffic:	Class	lass Regular							
	Type	FHCF	FHCF						
Pedestrian:	1.3m hi	gh railing at	railing at edge of bridge deck Median: N/A						
Between carriagew	ay and foo	otway:	FHCF						
Safety Screens:	N/A			Noise Walls:	N/A				
FHCF = Full Height Concrete Type F; TCF+1 = Truncated Type F + single RHS rail; TCF+2 = Truncated Type F + 2 RHS rail;									
TB = Thrie Beam	TB = Thrie Beam								

DURABILITY				
Exposure Classification:	B1 for superstructure, TBD for piles			
Soil/Water Aggressivity:	TBC			
Special durability measures (eg cathodic protection)	TBC			

SPECIAL REQUIREMENTS	Required ?	Report Details
Environmental (eg EIS, REF):	No	
Fisheries:	No	
Heritage:	No	
Navigation (MSB, DPW):	No	
Planning (DUAP):	Yes	
Other:	No	
Has Pier and Abutment position been pegged:	No	
Is more pegging required:	No	

OTB-TP-202-F62 Issue 11 (30 June 2008) Page 5 of 6

BRIDGE DESIGN PROPOSAL

Project No: Sketch No: 607207-001 File No:

CONCURRENCES										
Safety audit required?	,	Yes / No **	S	Safety audit completed?			Yes / No **			
Audit Details										
Concurrence in Road Design Aspects:										
Bridge geometry conforms to road design horizontal and vertical alignment, carriageway layout and cross falls						Yes / No **				
I have taken this proposal and the associated sketches to site, located the abutments and piers, and I confirm that the design represents the conditions on site and meets the project objectives.										
RTA Project Manager Design Manager ****	1		Dat				e:			
Concurrence with asset management aspects:										
Has risk assessment been done? Yes / No ** If no risk assessment, is one r						d?	Yes / No **			
Any additional requirements										
I have examined the [Design Propo	osal and consider	it satisfacto	ory to proceed with t	he Deta	ail Des	ign.			
RTA Regional Asset Manager										
'					'					
Concurrences noted:										
Supervising Bridge Engineer (New Design) / Design Manager ****				Da	te:					
** Strike through to delete **** Other than RTA Bridge Engineering in-house or managed designs										

OTB-TP-202-F62 Issue 11 (30 June 2008) Page 6 of 6

Annex 3 Indicative Material Schedule



Component	Material			
Superstructure				
Precast Plank	Reinforced Concrete, Lifting Anchor			
Cast In-situ Deck/Cycleway	Reinforced Concrete			
Shear Key	Sikagrout 100			
Bearing	Laminated Elastomeric Bearing, Elastomeric Bearing Strip			
Wearing Surface	Asphalt pavement			
Expansion Joint	AC Expansion Joint			
Joint Sealant	Sealent, Backing Rod, Bond Breaking Tape			
Substructure				
End Protection Beam	Reinforced Concrete, Lifting Anchor			
Precast Headstock	Reinforced Concrete, Lifting Anchor			
Precast Spun Piles	Reinforced Concrete			
Bridge Furniture				
Railing	Anchor Bolt, Washer, Nut, Base Plates, Steel Post			
Precast Barrier	Reinforced Concrete, Lifting Anchor			
Assembly / Connection				
Connection between planks	High tensile alloy steel bar, PVC Duct, O ring seal, Grout, Mortar, Threaded bar, Cast-in ferrule, Packing Plate, Rubber Strip, Polystyrene			
Connection between Spun Piles and Headstock	Support Bracket, Bolt, Steel Plate, Washer Plate			

Indicative Finished Treatment Schedule

Hoxton Park M-Lock Bridge Finished Treatment Schedule





Component	Treatment
M-Lock Planks	Class 2 Finish to AS3610
Cast-Insitu Deck / Cycleway	Class 2X Finish to AS3610
Precast Headstock	Class 2X Finish to AS3610
Precast Barriers	Class 2X Finish to AS3610
Precast Spun Piles	Class 2X Finish to AS3610
Metallic Components and Fixings	Painted or Hot-Dip Galvanised

Annex 5

Construction Methodology











Hoxton Park M-Lock Bridge Construction Methodology



Stage 1

Prepare the abutments where the piles and headstocks are located at each end of the bridge. This involves earthworks and compaction;

Construct Spill-through type embankment;

Stage 2

Survey all pile locations;

Pre -bored at the top of surface level;

Drive the pile to design depth and set;

Cut back the top of pile to the correct height;

Stage 3

Place precast headstock on top of piles;

Grout voids in precast headstock;

Stage 4

Drive piles for the next and subsequent pile groups;

Install remaining precast headstocks;

Stage 5

Place bearings on headstocks;

Position hold down bolts for planks;

Lift and position precast planks;

Lift and position concrete barrier units;

Stage 6

Bolt the legs of the planks together;

Transverse stressing of bars;

Grout the shear key;

Place expansion joint;


Place cycleway reinforcement, services, anchor bolts and railings;

Grout the transversely stressed bars;


Place asphalt pavement.

Annex 6


Photographs of Similar Structures




Twin (3 imes 10m span) M-Lock $^{ imes}$ bridges form the entry point to the Bella Vista Subdivision in Sydney



Three span (3 x 12m) M-LOCK $^{\otimes}$ bridge over the Bokhara River - Goodooga, NSW.



Topside of Bridge over the Bokhara River, Goodooga.



Completed 5 span (5 x 12m) M-LOCK $^{\otimes}$ Bridge over the Culgoa River - Goodooga, NSW.

Appendix C

RTA meeting minutes, general arrangements and in principle acceptance of proposed intersection treatments



MINUTES

Meeting

Hoxton Park - Part 3A Modification - Hinchinbrook Creek Link Road

Time

11:00am

Date

12 July 10

Location

RTA Offices - Parramatta

Pages

Present

Adrian Checchin, Stuart Penklis - Mirvac

Peter Johnson, Hugh Williams - ADW Johnson

Stan Kafes - CBHK

Ken Moon, James Hall, David Lance, Steve Acreman - RTA

Owen Hodgson, Wignes Wigneswaran - Liverpool City Council (LCC)

Dietribution

Those present, Jeff Organ - LCC, Adam Coburn - LCC

Distribution Those present, Jeff Organ – LCC, Adam Coburn – LCC				
Item	Description	Action		
1.0	Cowpasture Road Travelling Northbound (Intersection of proposed new Link Road)			
1.1	RTA confirmed a dedicated left turn lane onto the proposed new Link Road is required left from Cowpasture Road (no slip lane). This allows two through lanes on Cowapsture Road.	ADW Johnson		
1.2	Following 1.1, RTA confirmed that the left turn lane onto new the Link Road would not require a separating island between the left turn lane and through traffic lanes on Cowpasture Road. A left turn lane only without a separating island was deemed to be sufficient. This was requested by ADW Johnson as a result of surface drainage concerns. Discussions between all parties confirmed that pedestrian and cycle routes would not be affected by this item. RTA confirmed however that provision for a possible future Ped X would need to be made i.e. conduits only.	Note		
1.3	Mirvac advised that if the link Road was to be aligned adjoining the bus depot lot, land would need to be acquired from the bus depot owner in order for a slip lane to work. Mirvac and the RTA and Council acknowledged this was not a reality and that the intersection would need to be pushed further North. In this regard, the concept Link Road alignment would be reviewed. The left turn lane taper to commence from the bus depot boundary.	ADW Johnson		
1.4	Council acknowledged and accepted that 1.3 above would result in the Link Road not aligning the boundary of the bus depot land. Mirvac needs to check any environmental and archaeological issues relating to re alignment.	Mirvac		
1.5	Council advised it had only recently proposed to introduce possible playing fields north of the proposed intersection. In this regard, as a result of 1.4 above, impact of Link Road re-alignment to be overlaid on Council's proposed plan.	ADW Johnson		
1.6	Wignes Wigneswaran to forward CAD drawing of Council's proposed playing fields plans.	Wignes Wigneswaran		

2.0	Bus Depot Site - Land Owner - Ross Oliveri	
2.1	RTA and Council confirmed the existing access i.e. right into the bus depot travelling south on Cowpasture Road and left in and left out travelling north on Cowpasture Road is the access for the Bus depot.	Note
2.2	Accordingly, Mirvac does not need to design in or, allow for any future access connection from the bus depot to the proposed new Link Road.	
2.3	Council confirmed that any possible future access from the bus depot to the proposed new Link Road would be the owner of the bus depot site's responsibility.	,
3.0	Concept Proposal Tabled	
3.1	ADW Johnson to remove addition lane shown on Northern section of proposed new Link Road as not required (provide two right turn lanes and one left turn slip lane out of proposed new Link Road onto Cowpasture Road at the intersection). Single lane only in both directions is required for proposed new Link Road away from the intersection.	ADW Johnson
4.0	Location of New Intersection (Cowpasture Road / Proposed new Link Road)	
4.1	Location of intersection and its distance from the bus depot right in travelling south on Cowpasture Road to be checked to ensure appropriate.	Stan Kafes
5.0	Updated Concept Drawings & Traffic Modelling	
5.1	When complete, updated concept drawings & Traffic Modelling to be issued by Mirvac to RTA and Council.	ADW Johnson, Stan Kafes, Mirvac
6.0	Survey Information on Cowpasture Road	
6.1	RTA to provide any survey information on Cowpasture Road to ADW Johnson.	RTA
7.0	Cowpasture Road Travelling South bound (Intersection of proposed new Link Road)	

Prepared by:

satisfactory.

Adrian Checchin

7.1

12/7/10

The concept design allows for one right turn from Cowpasture Road onto the proposed new Link Road. RTA requested this be checked to ensure

Stan Kafes

Hugh Williams

From: MOON Ken E [Ken_MOON@rta.nsw.gov.au]

Sent: Friday, 30 July 2010 2:53 PM

To: Hugh Williams

Cc: Peter Johnson; ACREMAN Steve G; HALL James C; SELLATHURAI Pahee

Subject: RE: Hinchinbrook Creek Bridge and Cowpasture Road intersection

Hugh/Peter

I have checked the preliminary plans (150133 SK 010 B) showing a concept layout of a proposed new intersection with Cowpasture Rd from the Hoxton Park Airport redevelopment & agreement in principle is given to the plans. Once detailed plans have been developed including the signalisation of the intersection with Cowpasture Rd they will need to be forwarded to the RTA marked to the attention of James Hall who will arrange for their approval subject to you entering into a Works Authorisation Deed with the RTA & meeting all costs associated with their installation.

Regards Ken Moon Land Use Planning & Assessment Manager

From: Hugh Williams [mailto:hughw@adwjohnson.com.au]

Sent: Thursday, 29 July 2010 2:36 PM

To: MOON Ken E **Cc:** Peter Johnson

Subject: Hinchinbrook Creek Bridge and Cowpasture Road intersection

Ken

Attached are the preliminary general arrangement of the bridge crossing and TCS intersection with Cowpasture Road.

Any queries, please call.

Regards,

Hugh Williams
Senior Civil Engineer
ADW Johnson - Central Coast Office

2 Bounty Close, Tuggerah

PO Box 3717 Tuggerah N.S.W. 2259

Ph: (02) 4305 4300 Fax: (02) 4305 4399 Mob: 0413 804 603

Email: hughw@adwjohnson.com.au Website: www.adwjohnson.com.au

"THIS MESSAGE AND ANY FILES TRANSMITTED WITH IT ARE INTENDED FOR THE ADDRESSEE ONLY AND ARE TO BE USED ONLY FOR THE PURPOSES OF OUR CLIENTS INSTRUCTIONS. ANY FILES HEREWITH ARE COPYRIGHT OF ADW Johnson Pty Ltd. AND ARE NOT TO BE COPIED FOR ANY OTHER PURPOSE OR STORED ON A RETRIEVAL SYSTEM WITHOUT THE EXPRESS WRITTEN PERMISSION OF ADW Johnson Pty Ltd."

Before printing, please consider the environment. IMPORTANT NOTICE: This e-mail and any attachment to it are intended only to be read or used by the named addressee. It is confidential and

may contain legally privileged information. No confidentiality or privilege is waived or lost by any mistaken transmission to you. The RTA is not responsible for any unauthorised alterations to this email or attachment to it. Views expressed in this message are those of the individual sender, and are not necessarily the views of the RTA. If you receive this e-mail in error, please immediately delete it from your system and notify the sender. You must not disclose, copy or use any part of this e-mail if you are not the intended recipient.

